



S-OIL SEVEN ATF III

MULTI-PURPOSE AUTOMATIC TRANSMISSION OIL

Product Description

S-OIL SEVEN ATF III is for automatic or semi-automatic transmissions and torque converters of all passenger cars, light commercial vehicles and industrial vehicles, when the manufacturer requires an automatic transmission fluid (ATF) GM DEXRON III.

Applications

- Suitable for use all transmissions of trucks, buses and public works machineries when a fluid type ALLISON C-4 is required
- Hydraulic systems when a fluid type GM DEXRON III is required

Features and Potential Benefits

- Very high viscosity index linked with an excellent viscosity stability in operation
- Very low pour point
- Excellent thermal stability and resistance to oxidation

Performance Level

- GM TASA, DEXRON II(D/E), DEXRON III(G/H)
- Mazda ATF F-1
- CAT TO-2
- Ford MERCON
- ALLISON C-3/C-4/TES 389
- Volvo CE97340
- Vickers M2950-S, I-268-S

Typical Properties

Test Items	Method	Unit	Properties	
Specific Gravity	ASTM D1298	-	0.850	
Color	ASTM D1500	-	Red	
Viscosity	40°C	ASTM D445	cSt	35.1
	100°C	ASTM D445	cSt	7.48
Viscosity Index	ASTM D2270	-	228	
Flash Point	ASTM D92	°C	188	
Pour Point	ASTM D97	°C	-49	
Brookfield Viscosity	-40°C	ASTM D2983	cP	15,100

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

S-OIL SEVEN ATF III
2020.06.16

This lubricant used recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet is obtainable via your commercial adviser.